

ISOVER

CAVITY WALL SLAB 32

Declaration of Performance

Document No. IEINS114

 Certificate No. 0012-CPR-21v1
EN ISO 13162

1 Unique identification code of the product-type :

Cavity Wall Slab 32
See table here under.

2 Type, batch or serial number or any element allowing identification of the construction product as required under Article 11(4) of the CPR:

See product label

3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

Thermal Insulation for Buildings (ThIB)

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

Saint-Gobain Construction Products (IRL) Ltd.
Registered in Ireland, Company No. 11815
Unit 4 Kilcarbery Business park, Nangor Road,
Dublin 22; D22 R2Y7, Tel: +353 (0) 1 629 8400

5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) :

N/A

6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

System 1 (Reaction to fire)

System 3 (all other declared properties)

7 In case of the declaration of performance concerning a construction product covered by a harmonised standard :

Notified certification body Element Materials Technology Rotterdam B.V. No. 2812 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (2812-CPR-BA0053) for Reaction to fire.

8 Declared performance table: According to EN13162: 2012+A1:2015


Essential Characteristics	Performance	Abbrev.	Unit	Declared Performance			
Product Name				Cavity Wall Slab 32			
Reaction to fire	Reaction to fire	RtF	Euroclass	A1			
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)			NPD			
Acoustic absorption index	Sound absorption			NPD			
Impact noise transmission index	Dynamic stiffness			NPD			
	Thickness	d_t		NPD			
	Compressibility	c		NPD			
	Air flow resistivity	AF_r		NPD			
Direct airborne sound insulation index	Air flow resistivity	AF_r		NPD			
Continuous glowing combustion	Continuous glowing combustion (e)			NPD			
Thermal resistance	Thermal resistance	R_D	$m^2 K/W$	2.00	2.30	2.65	3.10
	Thermal conductivity	λ_D	$W/m K$	0.032	0.032	0.032	0.032
	Thickness	d_N	mm	65	75	85	100
	Thickness class	T_i		T4	T4	T4	T4
Water permeability	Short term water absorption	W_p	kg/m^2	WS	WS	WS	WS
	Long term water absorption	W_{ip}		NPD			
Water vapour permeability	Water vapour transmission	t or Z		NPD			
Compressive strength	Compressive stress or compressive strength	CS		NPD			
	Point load	F_p		NPD			
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics (a)		Euroclass	A1			
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance (b)	R_D	$m^2 K/W$	2.00	2.30	2.65	3.10
	Thermal conductivity (b)	λ_D	$W/m K$	0.032	0.032	0.032	0.032
	Durability characteristics (c)	d		NPD	NPD	NPD	NPD
Tensile/fluxural strength	Tensile strength perpendicular to faces (d)	TR		NPD			
Durability of compressive strength against heat, weathering, ageing/ degradation	Compressive Creep	Xct, Xt		NPD			

NPD No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products.
The fire performance of mineral wool does not deteriorate with time.
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

9 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Padraig Barry,
Managing Director,
Saint-Gobain Construction Products (Irl) Limited

October 2021

CONTACT DETAILS FOR FURTHER INFORMATION:

Please visit our website at: www.isover.ie

Contact details:

Free Phone (ROI): **1800 744480**

Free Phone (NI): **0845 3990159**

Email: tech.ie@saint-gobain.com

ISOVER is part of the Saint-Gobain group, leader in the design, production and distribution of materials for construction, industrial and consumer markets. ISOVER is the specialist in insulation within the group.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation.



SAINT-GOBAIN

ISOVER Ireland
Unit 4, Kilcarbery Business Park,
Nangor Road, Dublin 22
Tel: +353 (0)1 6298400
Email: info@isover.ie
www.isover.ie

Date of Publication: September 2021



ISOVER
SAINT-GOBAIN