

ISOVER ACOUSTIC ROLL

Declaration of Performance

 **Document No.**
DOP_A_ACOUSTIC_ROLL

1 Unique identification code of the product-type:

Acoustic Roll

See table here under...

2 Type, batch or serial number or anyother element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:

See product label

3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings (ThIB)

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Saint-Gobain Construction Products (IRL) Ltd. Registered in Ireland, Company No. 11815
Unit 4 Kilcarbery Business Park, Nangor Road,
Dublin 22; D22 R2Y7, Tel: +353 (0) 1 629 8400

5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1 (Reaction to fire)

System 3 (all other declared properties)

7 In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified certification body Element Materials Technology Rotterdam B.V. No. 2812 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (2812-CPR-BA0053 and 2812-CPR-BA10639) for Reaction to fire.

8 Declared performance table: According to EN13162: 2012+A1:2015

Essential Characteristics	Performance	Abbrev.	Unit	Declared Performance			
Product name				Acoustic Roll			
Product code				5200625536	5200625538	5200625546	5200643004
Reaction to fire	Reaction to fire	R _{tf}	Euroclass	A1			
Acoustic absorption index	Sound absorption			NPD			
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)			NPD			
Thermal resistance	Thermal resistance	R _D	m ² K/W	0.65	1.35	1.90	2.75
	Thermal conductivity	λ _D	W/mK	0.036	0.036	0.036	0.036
	Thickness	d _N	mm	25	50	70	100
	Thickness class	T _i		T1	T1	T1	T1
Impact noise transmission index	Dynamic stiffness			NPD			
	Thickness	d _L		NPD			
	Compressibility	c		NPD			
	Air flow resistivity	AF _r		NPD			
Direct airbourne sound insulation index	Air flow resistivity	AF _r		NPD			
Compressive strength	Compressive stress or compressive strength	CS		NPD			
	Point load	F _p		NPD			
Continuous glowing combustion	Continuous glowing combustion (e)			NPD			
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)		Euroclass	A1			
Durability of thermal resistance against ageing/degradation	Thermal resistance (b)	R _D	m ² K/W	0.65	1.35	1.90	2.75
	Thermal conductivity (a)	λ _D	W/mK	0.036	0.036	0.036	0.036
	Durability characteristics (c)	d		NPD			
Tensile/fluxural strength	Tensile strength perpendicular to faces (d)	TR		NPD			
Water permeability	Long term water absorption	W _{lp}		NPD			
Water vapour permeability	Water vapour transmission	t or Z		NPD			
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt		NPD			

NPD No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products.
The fire performance of mineral wool does not deteriorate with time.
The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

- 9 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Kieran Holohan,
Managing Director,
Saint-Gobain Construction Products (Irl) Limited

02/04/26

CONTACT DETAILS FOR FURTHER INFORMATION

Please visit our website at:
www.isover.ie

Email:
tech.ie@saint-gobain.com

Free Phone:
ROI 1800 744480 | NI 0845 3990159