





# ISOVER COMFORT 35 LANAÉ


A mineral wool insulation with a mineral wool tissue veil facing for even better workability when compared to standard unfaced insulation rolls.


## Where to use


-  Pitched Roof - Rafters
-  Pitched Roof - Attics
-  Framed construction


  
**CONTRIBUTES TO THERMAL PERFORMANCE**


  
**CONTRIBUTES TO ACOUSTIC PERFORMANCE**


  
**A2 REACTION TO FIRE CLASSIFICATION**


  
**VAPOUR PERMEABLE INSULATION**

  
**UP TO 60% RECYCLED GLASS**

  
**MINIMAL WASTE**

  
**EASY TO TRANSPORT**

  
**BIOSOURCED BINDER**

  
**EASIER TO CUT & INSTALL THAN UNFACED ROLLS**

Contributes to the above system performances as set out below.

## Features and Benefits\*

- ✓ **Thermal:** Thermal conductivity 0.035 W/mK. Contributes to energy performance to reduce heating and cooling costs.
- ✓ **Acoustic:** Contributes to system acoustic performance.
- ✓ **Fire:** A2 Reaction to Fire classification in accordance with EN 13501-1.
- ✓ **Easy to Install:** Comfort 35 Lanaé is easier to cut than standard unfaced insulation rolls due to its mineral wool tissue veil.
- ✓ **Environmental Credentials:** The new white Comfort 35 Lanaé is made from a 'Biosourced binder' in addition to up to 60% recycled glass. Mineral wool has been shown to have a low Carbon footprint relative to thermal performance.
- ✓ **Installed Performance:** Due to its fitability and inherent capacity for recovery at installation stage, glass mineral wool contributes to acoustic and thermal performance by naturally mitigating gaps within a framed construction or where installed in adjacent rolls to form a continuous layer above a ceiling. Following installation, the insulation should not be compressed by more than 10% to retain full thermal performance.

## Product Specification

Product	Product Code	Thickness (mm)	Width (mm)	Length (mm)	Pack Area (m <sup>2</sup> )	Packs per Pallet
Comfort 35 Lanaé	5200950540	140	1200	3400	4.08	24

\* When installed in accordance with our recommendations.

## Standards and Certification

<b>Quality</b>	Quality Management Standard EN ISO 9001: 2015 for manufacturing.
<b>CE</b>	Manufactured in accordance with the CE marking requirements under the Construction Products Regulation.
<b>Product Standards</b>	Manufactured in accordance with product standard: EN 13162:2012+A1:2015 and EN 13172 Evaluation of Conformity. Comfort 35 Lanaé is EUCEB-certified, which means, Isover mineral wool complies with the European Directive 97/67/EC showing that mineral wool is safe in production and use.
<b>Environment</b>	ISO 14001:2015 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system.
<b>Indoor Air Quality</b>	Comfort 35 Lanaé has earned Eurofins Indoor Air Comfort Gold certification, showing it meets Eurofins strictest air quality standards.
<b>Durability</b>	EN 13162 indicates that mineral wool - will not sustain vermin, nor breed or promote fungi or bacteria, - thermal conductivity does not change with time.
<b>Service Life</b>	As noted above in durability, based on sample dimensional stability testing, glass mineral wool installations are typically fit for purpose for the lifetime of the installation unless damaged.
<b>Repair</b>	Typically glass mineral wool will not require repair, though agitation of the material will assist recovery from local compression, alternatively, material may be easily replaced or topped up locally as required.
<b>Reusability</b>	Glass mineral wool insulation may be reused in suitable applications where respected in its use and preparation for reuse.
<b>Recyclability</b>	Glass wool insulation is circular due to its mineral composition, low wastage from installation, long life of the product and potential for reuse, glass wool is also recyclable with facilities available in Europe.
<b>Data Digitisation</b>	We have a BIM library for Isover products. System level information also available. Contact our Isover Technical Team for more information.
<b>Handling, Storage, Health and Safety</b>	Isover products are supplied fully palletised, offering ease of transport compared to unpalletised products. Information regarding storage and handling of Isover products and health & safety information can be found at <a href="http://www.isover.ie">www.isover.ie</a>



## Key Considerations

When incorporating into construction works, designers and installers should satisfy themselves that the product and the performances described in our literature are fit for the intended application.

Recovery guidance: Before installation, gently agitate the insulation by gently shaking or bouncing it on its side until it recovers to the thickness stated on the label.

## Safety Data Sheet

A Safety Data Sheet (SDS) for this product is available on <https://www.isover.ie/documents/safety-data-sheets/sds-isover-ireland-comfort-roll.pdf>



## CONTACT DETAILS FOR FURTHER INFORMATION

Email: [tech.ie@saint-gobain.com](mailto:tech.ie@saint-gobain.com) Free Phone: **ROI 1800 744480 | NI 0845 3990159**

Isover reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up to date library of information, visit [isover.ie](http://isover.ie)