



ISOVER SPACESAVER SOLID ROLL

A mineral wool roll for domestic attic floors.



**THERMAL
INSULATION**



**ACOUSTIC
INSULATION**



**EUROCLASS A1
FIRE RATING**



**FIRE
PROTECTION**



**MOISTURE
CONTROL**



BREATHABLE



**ENERGY
SAVINGS**



**EASY
TO INSTALL**



**RECYCLED
GLASS**



**PROTECTED
PLANET**



**MINIMAL
WASTE**



**EASY TO
TRANSPORT**

Features and Benefits

- ✓ **Thermal:** Conductivity 0.044 W/mK.
- ✓ **Acoustic:** Excellent Acoustic Performance.
- ✓ **Fire:** Excellent Fire Safety - A1 Fire Rated, highest possible rating. Completely fire safe - Euroclass A1 fire rating when classified in accordance with BS EN 13501-1.
- ✓ **Strength:** Excellent Recovery and strength.
- ✓ **Easy to install:** Friction fits between studs. Easy to install.
- ✓ **Environmental credentials:** Made from recycled glass. Minimal manufacturing and on-site wastage. Low carbon footprint at manufacture and during transport.

Standards and Certification

Quality	We hold a Quality Management Standard EN ISO 9001: 2015 for manufacturing.
CE	All products are manufactured in accordance with the CE marking requirements under the Construction Products Regulation.
Product Standards	All products are manufactured in accordance with product standard: EN 13162:2012+A1:2015 and EN 13172 Evaluation of Conformity.
Environment	Isover is an ISO 14001:2015 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system.
Indoor Air Quality	Awarded the highest standard in indoor air quality - Eurofins "Gold" Label The Gold Certificate means that Isover mineral wool is certified as an outstanding material in terms of Indoor Air Quality emissions regulations.
Durability	Fire Performance Euroclass classification of the product is related to the organic content, which cannot increase with time. Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air. (See std EN13162:2012 Annex ZA,Table ZA.1) Will not accelerate corrosion with steel, copper or aluminium. Will not sustain vermin, nor breed or promote fungi or bacteria.
Responsibly Sourced	Our products have been manufactured to BES60001 to ensure their constituent materials have been responsibly sourced.

Key Considerations

When using Isover Spacesaver, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Product Specification

Product	Product Code	Thickness (mm)	Width (mm)	Length (mm)	Pack Area (m ²)	Packs per Pallet
Spacesaver Solid	5200948358	100	1160	12180	14.13	24
Spacesaver Solid	5200666363	125	1200	6030	6.99	24
Spacesaver Solid	5200948361	150	1160	8050	9.34	24
Spacesaver Solid	5200948360	200	1160	5200	6.03	24



CONTACT DETAILS FOR FURTHER INFORMATION

Email: tech.ie@saint-gobain.com Free Phone: ROI 1800 744480 | NI 0845 3990159

Publish date: December 2023

Isover reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up to date library of information, visit isover.ie