



ISOVER VARIO® DOUBLEFIT+ MULTI-COMPONENT ADHESIVE SEALANT

The Vario® universal sealant - a solution for creating airtight joints between vapour membrane and adjacent surfaces.



**CONTRIBUTES
TO AIRTIGHTNESS
PERFORMANCE**



**CONTRIBUTES TO
ENERGY SAVINGS**



**EASY TO
TRANSPORT**

Contributes to the above system performances as set out below.

Features and Benefits*

- ✓ **Material:** 2 adhesive sealants based on modified acrylate dispersions.
- ✓ **Environmental Credentials:** Free of solvents, isocyanates, PVC, heavy metals and halogens.
- ✓ **Temperature Resistance:** From - 40°C to + 100°C.
- ✓ **Application Temperature:** From - 5°C to +40°C.
- ✓ **Curing Rate:** Approx. 2 mm/24h at 23 °C and 50% rel. humidity.
- ✓ **Resistant to Ageing:** Permanent elastic adhesive behaviour.
- ✓ **Shelf Life:** 24 months for a storage temperature from + 5 to + 35. Should be protected against UV radiation.
- ✓ **Suitable Substrate:** Masonry, concrete, aerated concrete, plaster, wood and metal.
The substrate must be clean, dry, free of grease and dust. The surface may need to be primed with a primer in cases of residue remaining after cleaning. Refer to 3rd party primer manufacturer's instructions for guidance.

* When installed in accordance with our recommendations.

Standards and Certification

Quality	Quality Management Standard EN ISO 9001: 2015 for manufacturing.
CE	Manufactured in accordance with the CE marking requirements under the Construction Products Regulation.
Environment	ISO 14001:2015 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system.
Indoor Air Quality	Vario® DoubleFit+ has been certified for indoor air quality and holds the GEV Eimicode EC1 Plus.

Product Specification

Product	Product Code	Width	Length	Per Roll	Pack	Packs per Pallet
Vario® Doublefit+ Mastic	5200645927	N/A	310ml	N/A	12 Cartridges	75 Boxes (900 Cartridges)

Safety Data Sheet

A Safety Data Sheet (SDS) for this product is available on
<https://www.isover.ie/documents/safety-data-sheets/sds-isover-ireland-varioudoublefit.pdf>



CONTACT DETAILS FOR FURTHER INFORMATION

Email: tech.ie@saint-gobain.com Free Phone: ROI 1800 744480 | NI 0845 3990159

Isover reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up to date library of information, visit isover.ie