



## ISOVER VARIO® DOUBLETWIN

A double-sided adhesive tape for fixing of vapour barriers to wood and metal substrates.



**CONTRIBUTES  
TO AIRTIGHTNESS  
PERFORMANCE**



**CONTRIBUTES TO  
ENERGY SAVINGS**



**EASY TO  
TRANSPORT**

Contributes to the above system performances as set out below.

### Features and Benefits\*

- ✔ **Material:** Polyacrylate-based dispersion adhesive.
- ✔ **Application:** Two-sided polyacrylate-tape for the adhesion of Vario® membranes to the Optima system.
- ✔ **Temperature Resistance:** From - 40°C to + 100°C.
- ✔ **Storage and Application Temperature:** From + 5°C to + 30°C.
- ✔ **Suitable Substrates:** For the adhesion of PA, PE, PP, PU, aluminium and paper foils. Adheres to the following substrates: wood, wood fibre boards, gypsum fibre boards, cement fibre boards, hard plastics and metal. The substrate must be clean, dry, free of grease and dust. The surface may need to be primed with a primer in cases of residue remaining after cleaning. Refer to 3rd party primer manufacturer's instructions for guidance.

\* When installed in accordance with our recommendations.

## Standards and Certification

<b>Quality</b>	Quality Management Standard EN ISO 9001: 2015 for manufacturing.
<b>CE</b>	Manufactured in accordance with the CE marking requirements under the Construction Products Regulation.
<b>Environment</b>	ISO 14001:2015 (Environmental Management System) accredited manufacturing facility. This accreditation ensures that all products are manufactured to the stringent standards set out by this management system.

## Product Specification

Product	Product Code	Width (mm)	Length (m)	Per Roll (m <sup>2</sup> )	Pack	Packs per Pallet
Vario® DoubleTwin	5200678235	19	50	0.95	15 Rolls	48 Boxes (720 Rolls)

## Safety Data Sheet

A Safety Data Sheet (SDS) for this product is available on <https://www.isover.ie/documents/safety-data-sheets/sds-isover-ireland-varioudoubletwin.pdf>



## CONTACT DETAILS FOR FURTHER INFORMATION

Email: [tech.ie@saint-gobain.com](mailto:tech.ie@saint-gobain.com) Free Phone: ROI 1800 744480 | NI 0845 3990159

Isover reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up to date library of information, visit [isover.ie](http://isover.ie)